

Elcometer 101 Coating Thickness Gauge



Elcometer 101 Coating Thickness Gauge

At a glance

• Available in 3 scale ranges.

Elcometer 101 Coating Thickness Gauge

The Elcometer 101 was the world's first portable coating thickness gauge which was first produced in 1947 and still has some advantages over other gauges.

- Insensitive to hot and cold surfaces – ideal for hot sprayed metal coatings
- Incorporates reading hold feature
- Accuracy of better than ±10%
- Ideal for hazardous areas

Coating Thickness Gauges – Mechanical

Mechanical Coating
Thickness Gauges are an
ideal choice when coating
thicknesses need to be
measured where batteries
cannot be used or are difficult
to obtain. For example in
remote locations, underwater,
where dangerous gasses are
present, you are looking for a
basic coating thickness gauge
to measure coatings on
Ferrous Substrates (e.g.
steel).

These gauges all use the original method of measurement – the amount of force needed to remove a magnet from a Ferrous Substrate and are basic coating thickness gauges to measure coatings on steel.

Minimum Substrate Thickness	1.5mm (60mils)	Operating Plane	90° to substrate
Minimum diameter for measurement on bar material	25mm (1")	Minimum Measurement Area	38 x 15mm (1.5 x 0.6")
Accuracy	Better than ±10% of the reading or ±2.5µm (0.1mils) whichever is the greater		

Model	Description	Range		Part Number
	Description	μm	Mils	rait Nullibei
Elcometer 101/05A	Elcometer 101 Mechanical Coating Thickness Gauge	0 - 250	0 - 10	A101A-05A
Elcometer 101/01A	Elcometer 101 Mechanical Coating Thickness Gauge	0 - 600	0 - 25	A101A-01A

data sheet

Related products



Elcometer 157



Elcometer 211



Elcometer 101/45

This simple pull-off gauge is a top pocket, lightweight, foreman's-type gauge for spot check indications of coating thickness. Insensitive to hot and cold coatings or surfaces - ideal for hot sprayed metal coatings for immediate results - also known as a pencil gauge.

The Elcometer 211, commonly referred to as the "Banana Gauge," has proven to be a successful coating thickness gauge where the use of electronic instruments is difficult, e.g. inflammable atmospheres in oil and gas production. The gauge can even be used underwater!

Whereas comparators allow the estimation of surface roughness by both touch and sight, the Elcometer 101 estimates the roughness of iron and steel surfaces. Its scale indicates the suitability of the surface for paints, metal coatings and hard metal coatings.

elcometer

ENGLAND

Elcometer Ltd Edge Lane Manchester M43 6BU

Tel: +44 (0)161 371 6000 Fax: +44 (0)161 371 6010 e-mail: sales@elcometer.com www.elcometer.com

USA

Elcometer Inc 1893 Rochester Industrial Drive Rochester Hills Michigan 48309

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: inc@elcometer.com www.elcometer.com

CANADA

Elcometer Ltd PO Box 622, 401 Ouelette Avenue Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: ca_info@elcometer.com www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd 896 Dunearn Rd Sime Darby Centre #3-09 Singapore 589472, Republic of Singapore

Tel: +65 6462 2822 Fax: +65 6462 2860 e-mail: asia@elcometer.com www.elcometer.com

BELGIUM

Elcometer SA Rue Vallée 13 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10 Fax: +32 (0)4 374 06 03 e-mail: be_info@elcometer.be www.elcometer.be

FRANCE

Elcometer Sarl 97 Route de Chécy 45430 BOU

Tel: +33 (0)2 38 86 33 44 Fax: +33 (0)2 38 91 37 66 e-mail: fr_info@elcometer.fr www.elcometer.fr

GERMANY

Elcometer Instruments GmbH Ulmer Strasse 68 D-73431 Aalen

Tel: +49 (0)7361 52806 0 Fax: +49 (0)7361 52806 77 e-mail: de_info@elcometer.de www.elcometer.de