

Elcometer 129 Rubert & Rugotest Surface Comparators



Elcometer 129 Rubert & Rugotest Surface Comparators

At a glance

- Estimate surface roughness by touch and sight.
- Available in grit and shot.

Elcometer 129 Rubert & Rugotest Surface Comparators

Comparators allow the estimation of surface roughness by both touch and sight.

The Elcometer 129 Rubert Comparators are available in two models:

- The Elcometer 129 Rubert available in Grit and Shot Versions
- The Elcometer 129 Rugotest includes the shot and grit profiles on the same block
- Available in metric units only
- Roughness is displayed on both classes and groups for easier identification

Surface Profile

The proper and effective preparation of a surface prior to coating is essential. Making sure that the correct roughness – or profile – has been generated is essential.

If the profile is too low, the adhesion of the coating to the surface will be reduced. Too high and there is the danger that the profile peaks will remain uncoated – allowing rust spots to occur.

Can be used in accordance with:

ASTM D 4417 Method A

	Elcometer 129/1 Rubert Grit Elcometer	Elcometer 129/2 Rubert Shot Elcometer	Elcometer 129/3 Rugotest Shot and Grit
Section Profiles	0.4, 0.8, 1.6, 3.2, 6.3 and 12.5µm	0.4, 0.8, 1.6, 3.2, 6.3 and 12.5µm	N6, N7, N8, N9, N10 and N11 equivalent to 0.8, 1.6, 3.2, 6.3, 12.5 & 25µm roughness averages respectively
Part Numbers	E1291	E1292	E1293

data sheet

Related products



Elcometer 125

Surface comparators allow the estimation of surface roughness by both touch and sight. These simple roughness gauges consist of 4 blasted profiles of varying roughness and are available either in a grit blasted or a shot blasted version.



Elcometer 127

These comparators from Keane-Tator are designed to be used with a magnifier. Consisting of 5 blasted profiles on displayed with the roughness value on each disc. In the middle of the disc there is a hole for the comparison to be undertaken using the magnifier. Sand, shot or grit versions available.



Elcometer 124

The Elcometer 124 thickness gauge is used to measure the peak-to-valley height of a surface profile formed in the Elcometer 122 Testex Tape.



Elcometer 122



Elcometer 101/45

The Elcometer 122 testex tape allows the user to measure the peak-to-valley height of the profile and record it. Testex tape consists of foam with a non-compressible backing. The foam side is rubbed into the surface providing a permanent mould of the profile. The Elcometer 124 Thickness Gauge is then used to measure the peak-to-valley height of the profile formed.

Whereas comparators allow the estimation of surface roughness by both touch and sight, the Elcometer 101 estimates the roughness of iron and steel surfaces. Its scale indicates the suitability of the surface for paints, metal coatings and hard metal coatings.



Elcometer 223

The Elcometer 223 is a battery operated digital surface profile gauge which measures the peak-to-valley height of a surface in a similar way to the Elcometer 123 analogue equivalent, but with the added benefit of a direct RS232 output for data logging.

elcometed

ENGLAND

Elcometer Ltd Edge Lane Manchester M43 6BU

Tel: +44 (0)161 371 6000 Fax: +44 (0)161 371 6010 e-mail: sales@elcometer.com www.elcometer.com

USA

Elcometer Inc 1893 Rochester Industrial Drive Rochester Hills Michigan 48309

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: inc@elcometer.com www.elcometer.com

CANADA

Elcometer Ltd PO Box 622, 401 Ouelette Avenue Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: ca_info@elcometer.com www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd 896 Dunearn Rd Sime Darby Centre #3-09 Singapore 589472, Republic of Singapore

Tel: +65 6462 2822 Fax: +65 6462 2860 e-mail: asia@elcometer.com www.elcometer.com

BELGIUM

Elcometer SA Rue Vallée 13 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10 Fax: +32 (0)4 374 06 03 e-mail: be_info@elcometer.be www.elcometer.be

FRANCE

Elcometer Sarl 97 Route de Chécy 45430 BOU

Tel: +33 (0)2 38 86 33 44 Fax: +33 (0)2 38 91 37 66 e-mail: fr_info@elcometer.fr www.elcometer.fr

GERMANY

Elcometer Instruments GmbH Ulmer Strasse 68 D-73431 Aalen

Tel: +49 (0)7361 52806 0 Fax: +49 (0)7361 52806 77 e-mail: de_info@elcometer.de www.elcometer.de