

Elcometer 213/2 Digital Waterproof Thermometer



Elcometer 213/2

The Elcometer 213/2 Digital waterproof thermometer has been specifically designed for superior durability and ease of use.

With an extruded aluminium case which is waterproof to IP66 & IP67 and a range of interchangeable probes, the Elcometer 213/2 offers a versatile instrument for measuring surface and liquid temperatures.

Features of the Elcometer 213/2 Digital Thermometer include:

- **Temperature probes:**
Magnetic Surface Probe, Surface Probe, Liquid Probe and Needle Probe.
- **Durable and waterproof case:**
Made from extruded aluminium for superior durability. The case is waterproof, offering IP66/67 protection.
- **Switchable units:**
°C / °F switchable.
- **Quick response time:**
Readings are displayed on the LCD screen within 1 second (approximately).

Climatic Condition Testing

During the application of a coating, the presence of moisture in the environment, or on the work surface, often results in a poor quality finish. Problems such as poor adhesion of the coating, delayed drying time or premature corrosion of the substrate can occur.

Before proceeding, it is essential that the air temperature and relative humidity (RH) are measured to calculate the dewpoint. The difference between this and the surface temperature is displayed as ΔT , with a warning if necessary.

At a glance:

Easy to use digital thermometer

Can be used to measure surface, liquid or soft material temperatures

IP66/67 waterproof case

| | |
|------------------------|--|
| Accuracy | ±1% of the reading ± 1 digit |
| Resolution | 0.1°C (0.1°F) up to +299.9°C (+ 599.9°F) 1°C (1°F) above +299.9°C (+ 599.9°F) |
| Power Supply | 1 x MN1604/PP3 (9V) Battery |
| Battery Life | 5,000 hours |
| Operating Range | -49°C to 1372°C (-56°F to 2500°F) [†] |
| Display | 12mm LCD Display |
| Dimensions | 35 x 60 x 115mm (1.4" x 2.4" x 4.5") |
| Weight | 194g (0.42lb) |
| Packing List | Elcometer 213/2 Digital Thermometer with battery fitted and operating instructions Probes are not supplied as standard with the Elcometer 213/2. Please select the required probe from the list below. |
| Part Number | G213----2 |

[†] Operating range is dependant on probe used

| Probes | | |
|-------------|--|-------------------------------|
| Part Number | Description | Maximum Operating Temperature |
| T21311728 | Magnetic Surface Probe (13mm diameter) | 150°C / 302°F |
| T2136069- | Surface Probe (130 x 4.2mm diameter) | 600°C / 1112°F |
| T9996390- | Liquid Probe (130 x 3mm diameter) | 850°C / 1562°F |
| T2136391- | Needle Probe (130 x 3mm diameter) | 400°C / 752°F |

Other probes are available on request. Contact Elcometer for further information.

ENGLAND
 Elcometer Limited
 Edge Lane
 Manchester M43 6BU
 Tel: +44 (0)161 371 6000
 Fax: +44 (0)161 371 6010
 e-mail: sales@elcometer.com
 www.elcometer.com

USA
 Elcometer Inc
 1893 Rochester Industrial Drive
 Rochester Hills Michigan 48309

Tel: +1 248 650 0500
 Toll Free: 800 521 0635
 Fax: +1 248 650 0501
 e-mail: inc@elcometer.com
 www.elcometer.com

ASIA & THE FAR EAST
 Elcometer (Asia) Pte Ltd
 896 Dunearn Rd
 Sime Darby Centre #3-09
 Singapore 589472,
 Republic of Singapore

Tel: +65 6462 2822
 Fax: +65 6462 2860
 e-mail: asia@elcometer.com
 www.elcometer.com

BELGIUM
 Elcometer SA
 Rue Vallée 13
 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
 Fax: +32 (0)4 374 06 03
 e-mail: be_info@elcometer.be
 www.elcometer.be

FRANCE
 Elcometer Sarl
 97 Route de Chécy
 45430 BOU

Tel: +33 (0)2 38 86 33 44
 Fax: +33 (0)2 38 91 37 66
 e-mail: fr_info@elcometer.fr
 www.elcometer.fr

GERMANY
 Elcometer Instruments GmbH
 Ulmer Strasse 68
 D-73431 Aalen

Tel: +49 (0)7361 52806 0
 Fax: +49 (0)7361 52806 77
 e-mail: de_info@elcometer.de
 www.elcometer.de

Related products



Elcometer 319

Elcometer 319 Dewpoint Meter

Available in two models, Standard and Top, the Elcometer 319 has been specifically designed to measure and record all relevant climatic parameters required to determine whether conditions are suitable for painting. It's rugged and ergonomic design is dustproof and waterproof equivalent to IP66 and incorporates fully sealed, durable sensors.

The Elcometer 319 Top has a large inbuilt memory to accurately record each measurement, storing up to 25,000 sets of readings in 999 batches. It also offers USB data output and *Bluetooth*[®] wireless technology for cable free data transfer.



Elcometer Inspection Kits

Elcometer Inspection Kits

Site inspection requires a range of portable testing equipment. In order to make these products easily available and transportable, Elcometer have developed a range of inspection kits. All the gauges are conveniently stored in a hard plastic protective carrying case and are supplied with full operating instructions.