

Elcometer 345 Coating Thickness Gauge



Elcometer 345 Coating Thickness Gauge

At a glance

- Simple, easy-to-use digital coating thickness gauge.
- Ferrous, Non-Ferrous & Dual-Ferrous versions available.
- Supplied complete with probe and foils.

Elcometer 345 Coating Thickness Gauge

The Elcometer 345 Coating Thickness Gauge is an incredibly versatile gauge.

With a range of probes in both Integral or Separate probe versions for coating thickness measurements on Ferrous (F), Non Ferrous (NF) or both Ferrous and Non Ferrous (FNF) Substrates, the Elcometer 345 will have a gauge for your requirements.

The gauge is easy to use and has been designed with the operator in mind. User definable simple statistics allows the user to view average, standard deviation, number of readings, maximum and minimum thickness readings. These statistics can be printed out.

- Keylock™ feature to avoid accidental recalibration
- Switchable between microns or mm & mils
- Bigfoot™ for stability on integral models
- Ideal for flat, curved and blasted surfaces
- Fast reading rate
- Two point calibration

Coating Thickness Gauges- Digital

Simple to interpret, small and portable gauges for the measurement of coatings on all metal surfaces. Digital coating thickness gauges are more accurate, more repeatable and more reproducible than any other type of coating thickness gauge on the market today.

Elcometer offers the world's most comprehensive range of portable digital coating thickness gauges - for measurements on either Ferrous substrates (F), Non-Ferrous substrates (NF), or on both Ferrous and Non-Ferrous (FNF), Elcometer can provide you with a gauge to meet your need.

With a wide choice of gauges to choose from, the User needs to understand the terminology of Coating Thickness Gauges or, 'The Language of CTGs'.

THE LANGUAGE OF CTGs

In selecting the most appropriate gauge for your application, you need to answer specific questions.

1. What is the substrate (the surface metal) you are coating/inspecting?

Is the metal a Ferrous Substrate (F) or a Non-Ferrous (NF)? Sometimes this is difficult to answer – the substrate may have already been coated .The easiest way to identify this is to see if a magnet will stick to the surface. If it does, then the substrate will be Ferrous, if it does not, then the substrate is Non-Ferrous.

2. Do you measure only on this substrate?

If you only inspect one type of product, then the answer is yes. If you have a range of products that you inspect, then you need to consider whether they are all of the same type of substrate. You should also consider if you have a future possibility of inspecting other substrates. If so, you should consider an FNF gauge.

Can be used in accordance with:		
FERROUS (F)	NON-FERROUS (NF)	DUAL FERROUS and NON-FERROUS (FNF)
ASTM B 499 BS 5411-11 BS 3900-C5-6Aa BS EN ISO 1461 DIN 50981 ISO 2178 ISO 2808-6Aa prEN ISO 19840	ASTM D 1400 ASTM B 244 BS 5411-3 BS 3900-C5-6Ba BS 5599 DIN 50984 ISO 2360 ISO 2808-6Ba	All of the Ferrous and Non-Ferrous List plus; ASTM E 376

Description	Range		Resolution		Accuracy*		Part Number
	µm	mils	Metric	Imperial	Metric	Imperial	
Elcometer 345 Ferrous Integral	0 – 1500	0 – 60	0.1µm up to 20µm	0.01mil up to 1.0 mils	±1-3% or 2.5µm	±1-3% or ±0.1mils	A345FB-I1
Elcometer 345 Ferrous Separate	0 – 1500	0 – 60					A345FB-S1
Elcometer 345 Non-Ferrous Integral	0 – 1500	0 – 60	0.1µm up to 20µm	0.01mil up to 1.0 mils	±1-3% or 2.5µm	±1-3% or ±0.1mils	A345NB-I1
Elcometer 345 Non-Ferrous Separate	0 – 1500	0 – 60					A345NB-S1
Elcometer 345 Dual FNF Integral**	0 – 1500	0 – 60	0.1µm up to 20µm	0.01mil up to 1.0 mils	±1-3% or 2.5µm	±1-3% or ±0.1mils	A345FNFB11
Elcometer 345 Dual FNF Separate**	0 – 1500	0 – 60					A345FNFB51

*1% when calibrated close to the required thickness, 3% across the range
 ** FNF Patent Number GB 2306009B. USA 5886522

3. What is your Coating / Substrate Combination?

Ensure compatibility of the coating and substrate; whether a coating thickness gauge will provide an accurate reading.

4. Typically what sort of coating thickness do you need to measure?

This will help you select the correct probe scale range - e.g. Scale 1 measures coatings up to 1500µm (60mils).

5. What type of probe do you need?

Depending on your application you can select from:

- Integral Probe (the probe is built into the gauge for accurate single handed measurements on large surface areas, pipes, etc.)
- Separate Probe (the probe is connected to the gauge by a cable for all applications).
- PINIP™ (the separate probe is directly attached to the base of the instrument – providing, in your separate gauge, all the benefits of an integral unit).

Separate Probes can be selected from our wide range to meet your application requirements. These include:

- *Regular Probes*: Including Straight, Right Angle (90°) and Telescopic options
- *Miniature Probes*: Including Straight, Right Angle (90°), 45° Angle all in either long or short versions.

6. Do you need to save your readings for your ISO records, or as proof of inspection to your customer?

Elcometer gauges are available in three options:

- *Basic Gauge* -with simple statistics but no memory or data output
- *Standard Gauge* -with statistics, limited memory and data output
- *Top Gauge* -with statistics, enhanced memory, batching capability and data output

Related products



Elcometer 345 SSG

The Elcometer 345 Gauge has been specifically designed for the Steel Structures Industry for measuring the coating thickness on structural steel. It can be used to test the wide variety of coatings and coating systems used on bridges, ships, buildings, etc. The Elcometer 345 SSG comes complete with a one year warranty.



Elcometer 456

With its recently enhanced and simplified menu screen options, the Elcometer 456 remains the most advanced hand held coating thickness gauge on the market today. This flagship product is available in any combination of Basic, Standard and Top functionality; together with Integral (built in) and an extensive range of separate plug in probes. With such an extensive range of gauge options, there is an Elcometer 456 to meet your specific application needs.



Elcometer 355

Accuracy, simplicity, versatility and flexibility are the watchwords of the Elcometer 355, a truly state of the art hand-held measuring system packed with time-saving and cost cutting features. The key to the superiority of the Elcometer 355 is its measuring system which features a range of interchangeable Probe Modules capable of an accuracy of $\pm 1\%$ of the reading on a variety of coatings and substrates.

ENGLAND

Elcometer Ltd
Edge Lane
Manchester M43 6BU

Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com
www.elcometer.com

USA

Elcometer Inc
1893 Rochester Industrial Drive
Rochester Hills Michigan 48309

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com
www.elcometer.com

CANADA

Elcometer Ltd
PO Box 622, 401 Ouelette Avenue
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: ca_info@elcometer.com
www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
896 Dunearn Rd
Sime Darby Centre #3-09
Singapore 589472,
Republic of Singapore

Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com
www.elcometer.com

BELGIUM

Elcometer SA
Rue Vallée 13
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.be
www.elcometer.be

FRANCE

Elcometer Sarl
97 Route de Chécý
45430 BOU

Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.fr
www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
Ulmer Strasse 68
D-73431 Aalen

Tel: +49 (0)7361 52806 0
Fax: +49 (0)7361 52806 77
e-mail: de_info@elcometer.de
www.elcometer.de