

# Elcometer 6910 Setaflash “Series 3” Closed Cup Tester



Elcometer 6910 Setaflash “Series 3” Closed Cup Tester

### At a glance

- *Ease of operation with minimum skill required.*
- *Digital Display.*
- *Extended operating temperature range, from 0 to 300°C (32 to 572°F).*
- *Thermally activated to detect flash point and reduce risk of inhaling fumes and operator error.*
- *Rechargeable gas tank.*

Can be used in accordance with:	
ASTM D 13278	ASTM D 3828-IP303
BS3900 Part A13	EN456
ISO 3680	ISO 3679
UN Class 3 Non-viscous flammable liquids	

### Elcometer 6910 Setaflash “Series 3” Closed Cup Tester

Combining the latest design standards with the highly successful Setaflash Tester, the new Setaflash Series 3 offers the fastest and most accurate flash point instrument at a cost effective price.

A range of unparalleled features ensures ease of operation and requires a minimum of operator skill. Test parameters are set via the key pad and a digital display provides temperature, sample size, test time, and flash detection status. Default 'auto' values are available for standard test conditions.

An extended operating temperature range allows tests from 0 to 300°C (32 to 572°F)\*. Temperature is factory calibrated but facilities for user verification and calibration are incorporated. Flash point is automatically detected using a thermally activated detector, reducing the risk of operator error and minimising the potential danger of inhaling fumes during a test. A rechargeable gas tank with on/off switch and fine adjustment are integral to the unit. Supplied with a 2ml syringe and ignitor.

\* *Additional Cooling Module required.*

### Flash Point

When developing any solvent based liquids such as coatings or perfumes, it is imperative that you determine the flashpoint to meet the stringent regulations laid down by most governments around the world and declare it on the material safety data sheet.

# Elcometer 6910 Setaflash “Series 3” Open Cup Tester



Elcometer 6910 Setaflash “Series 3” Open Cup Tester

**At a glance**

- Open cup for with of without flash finite determinations.
- Cup fitted with manual flame sweeping arm.
- Control valve supplies gas to the integral tank.
- Pass the test flame over the sample to view the combustion characteristics.

**Elcometer 6910 Setaflash “Series 3” Open Cup Tester**

Certain substances classified as Flammable by Closed Cup Flash Point Testing may be reclassified as non-flammable by combustibility testing. This has significant potential cost implications for the packaging storage and shipping of many materials.

Generally similar to the 6910 Setaflash, but with an open cup for flash/no flash, finite determinations or sustained combustion tests. A manually operated flame sweeping arm is fitted to the cup and gas is supplied from the integral tank via the control valve. The flash or sustained combustion characteristics of the sample are observed visually by passing the test flame over the sample.

Can be used in accordance with:	
ASTM D 13278	ASTM D 3828-IP303
BS3900 Part A13	EN456
ISO 3680	ISO 3679
UN Class 3 Non-viscous flammable liquids	

<b>Voltage</b>	115/220V (switchable)
<b>Temperature Range</b>	Elcometer 6910/1 Closed Cup Tester: Ambient to 300°C (572°F). 0 to 300°C (32 to 572°F) when used with Cooling Module  Elcometer 6910/2 Open Cup Tester: Ambient to 300°C (572°F).
<b>Sample Size</b>	2ml for flash points up to 100°C (212°F) 4ml for flash points between 100 to 300°C (212 to 572°F)
<b>Test Time</b>	1 to 99 minutes
<b>Default Values</b>	1 minute for flash points up to 100°C (212°F) 2 minutes for flash points between 100 to 300°C (212 to 572°F)
<b>Cup Material</b>	Aluminium
<b>Dimensions</b>	25.6 x 28 x 25.6cm (10.08 x 11.02 x 10.08")
<b>Weight</b>	4 kg (8.8lb)

Model	Description	Part Number		
		UK 240V	EUR 220V	US 110V
Elcometer 6910/1	Setaflash Series 3 Closed Cup Tester	K0UK6910M010	K0006910M010	K0US6910M010
Elcometer 6910/2	Setaflash Series 3 Open Cup Tester	K0UK6910M011	K0006910M011	K0US6910M011
<b>Accessories</b>	Cooling Module for Elcometer 6910/1 Allows tests from 0 to 300°C (32 to 572°F).	KT006910N001		

**ENGLAND**

Elcometer Ltd  
Edge Lane  
Manchester M43 6BU

Tel: +44 (0)161 371 6000  
Fax: +44 (0)161 371 6010  
e-mail: sales@elcometer.com  
www.elcometer.com

**USA**

Elcometer Inc  
1893 Rochester Industrial Drive  
Rochester Hills Michigan 48309

Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: inc@elcometer.com  
www.elcometer.com

**CANADA**

Elcometer Ltd  
PO Box 622, 401 Ouelette Avenue  
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: ca\_info@elcometer.com  
www.elcometer.com

**ASIA & THE FAR EAST**

Elcometer (Asia) Pte Ltd  
896 Dunearn Rd  
Sime Darby Centre #3-09  
Singapore 589472,  
Republic of Singapore

Tel: +65 6462 2822  
Fax: +65 6462 2860  
e-mail: asia@elcometer.com  
www.elcometer.com

**BELGIUM**

Elcometer SA  
Rue Vallée 13  
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10  
Fax: +32 (0)4 374 06 03  
e-mail: be\_info@elcometer.be  
www.elcometer.be

**FRANCE**

Elcometer Sarl  
97 Route de Chécy  
45430 BOU

Tel: +33 (0)2 38 86 33 44  
Fax: +33 (0)2 38 91 37 66  
e-mail: fr\_info@elcometer.fr  
www.elcometer.fr

**GERMANY**

Elcometer Instruments GmbH  
Ulmer Strasse 68  
D-73431 Aalen

Tel: +49 (0)7361 52806 0  
Fax: +49 (0)7361 52806 77  
e-mail: de\_info@elcometer.de  
www.elcometer.de